

SmartLF Scan! series

PORTABLE CONVENIENCE WITH BUILT-IN CONTROLLER

Finally, a low-cost, large format scanner that works both as a networked office scanner and on the road. Use it on site, in your office or in your home. With 4 ways to move and store digitised information, it couldn't be easier. Store in the scanner; save to a USB stick; or transfer to a standalone or networked PC.



IDEAL FOR THESE
DOCUMENT TYPES

TECHNICAL

SmartLF Scan! series



© Colortrac / 01-2023 / V1.2 EN

Model name	Scan! 24	Scan! 36
Imaging technology	SingleSensor	SingleSensor
Maximum scan width	24 in (607 mm)	36 in (914 mm)
Maximum media width	26 in (660 mm)	38 in (965 mm)
Scanning speed full width document:		
200 dpi monochrome	4.5 in/sec (114 mm/sec)	
200 dpi color	3 in/sec (76 mm/sec)	
Productivity in batch scanning ISO A0/Arch E-size (or widest) for 60 minutes. Includes paper load and eject time. Measured in completed scans:		
Portrait, 200 dpi	Monochrome: 219 docs/hour. Color: 167 docs/hour	
Specifications:		
Maximum media thickness	0.02 in (0.5 mm)	
Maximum optical resolution	Automatic (DocLogic). Manual: 200, 400, 600 dpi	
Total number of pixels	28800	43200
Colortrac key technologies	SingleSensor	
Document justification	Centre	
Accuracy	0.2% +/-1 pixel	
Data capture color depth inside scanner	48-bit color, 16-bit monochrome	
Color spaces	sRGB	
Maximum image length	200 in (5 m) @200 dpi, 150 in (3.8 m) @400 dpi, 109 in (2.7 m) @600 dpi. (DocLogic reserves 300 dpi)	
USB interface	USB 2.0 – scanning to memory stick	
Ethernet interface	GigaBit – scanning to networked PC	
Memory	6 GB or 8 scans	
Bundled software	NetApp (network scan collection utility) Free download	
Optional software	N/A	
File formats	TIFF, JPEG, PDF	
File compatibility	AutoCAD (as raster), CAD, GIS and other raster image editing/storage applications	
Printer support	Print from any viewer using Windows printer driver	
Operating systems	Windows 11 64-bit and Windows 10 64-bit and 32 bit	
Power consumption	19.4 W/ 0.3 W/0.05 W (soft OFF)	
External power supply	100~240 VAC auto-sensing +/-10%, 50-60Hz, output: 3.42 A at 19 V	
Operating conditions (environmental)	10–35°C, 35–90% relative humidity (non-condensing)	
Weight	Unpacked: 11.5 lbs. (5.2 kg). Packed: 22.3 lbs. (10.1 kg)	Unpacked: 15.4 lbs. (7 kg). Packed: 30.9 lbs. (14 kg)
Dimensions W×H×D	Unpacked: 34.3×6.3×5 in (87×16×12.6 cm) Packed: 38.6×10.4×8.2 in (98×26.5×20.8 cm)	Unpacked: 46.3×6.3×5 in (117.5×16×12.6 cm) Packed: 50.4×10.4×8.2 in (128×26.5×20.8 cm)
Certifications/compliance	ENERGY STAR® certified, CB, CE, CCC, FCC, UL, RoHS compliant	
Country of origin	Designed and engineered in Denmark, Europe. Manufactured in China.	

Colortrac® is a Global Scanning brand. Colortrac® makes no warranty of any kind with respect to the information contained in this document and reserves the right to change specifications without notice. Colortrac® and SmartLF® are trademarks of Global Scanning. All other trademarks are the property of their respective owners.

ACCESSORIES

- Includes everything you need to use SmartLF Scan!
- Ruggedised, wheeled carrying case for ultimate portability
 - Ethernet cable to connect to your PC or network
 - Instruction manual
 - Power cables
 - Calibration sheet



NO NONSENSE

- Accurately scan large format documents from your live projects and output to three file types:
- PDF for collaboration – everyone can open
 - JPEG for compression – great for email
 - TIFF for analysis – raw, full-size uncompressed images



colortrac.com/smartlfscan

Colortrac HQ & EMEA: Global Scanning UK Ltd., St Ives, UK, info@colortrac.com
 Colortrac Americas: Global Scanning Americas Inc., Chantilly, VA, USA, +1 (703) 717 5325
 Colortrac Japan & Asia: Global Scanning Japan A/S, Yokohama-Shi, Japan, +81 45 548 6991

